

**DECLARATION OF PERFORMANCE
UKCA 81**



1. Product Type: **Armpave 60 (60mm Rectangular Paving Blocks)**
2. Identification: **Product ID code is shown on delivery ticket**
3. Intended Use: **Precast concrete paving block for use in external flooring applications**
4. Manufacturer: **Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY**
5. Authorised Representative: **Not applicable**
6. AVCP: **System 4**
7. Designated Standard: **BS EN 1338:2003**
8. ETA: **Not Relevant**
9. Declared Performance:

| Essential Characteristics | Performance | Designated technical specification | |
|---------------------------|--------------------------|------------------------------------|---|
| Intended Use | External Flooring | BS EN 1338:2003 | |
| Emission of Asbestos | X | | |
| Breaking Strength | 3.6 MPa | | |
| Slip/Skid Resistance | Satisfactory | | |
| Thermal Conductivity | X | | |
| External Fire Performance | X | | |
| Durability | Abrasion | | 4 |
| | Resistance to Weathering | | 2 |
| Reaction to fire | X | | |

X = Not Relevant

10. The performance of the product identified in 1 and 2 is in conformity with the declared performance in 9.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed on behalf of the manufacturer: *J Mason* Brompton-on-Swale, North Yorkshire.
J Mason (Technical Manager) 1st August 2021



**Thomas Armstrong (Holdings) Ltd Workington Rd,
Flimby, Maryport, Cumbria. CA15 8RY**

21

UKCA 81

BS EN 1338:2003

Armpave 60 (60mm Rectangular Paving Blocks)

Category II Concrete Paving Blocks

| | |
|---------------------------|-------------------|
| Intended Use | External Flooring |
| Emission of Asbestos | X |
| Breaking Strength | Pass |
| Slip / Skid Resistance | Satisfactory |
| Thermal Conductivity | X |
| External Fire Performance | X |
| Durability | Satisfactory |
| Reaction to fire | X |

X = Not Relevant

See Declaration of Performance

UKCA 81