DECLARATION OF PERFORMANCE UKCA 90



1. Product Type: Boot Kerb

2. Identification: Product ID code is shown on delivery ticket

3. Intended Use: Precast concrete paving block for use in external flooring

applications

4. Manufacturer: Thomas Armstrong (Holdings) Ltd Workington Rd,

Flimby, Maryport, Cumbria. CA15 8RY

5. Authorised Representative: Not applicable

6. AVCP: System 4

7. Designated Standard: BS EN 1338:2003

8. ETA: Not Relevant

9. Declared Performance:

| Essential Characteristics | | Performance | Designated technical specification |
|---------------------------|--------------------------|-------------------|------------------------------------|
| Inended Use | | External Flooring | BS EN 1338:2003 |
| Emission of Asbestos | | x | |
| Breaking Strength | | 3.6 MPa | |
| Slip/Skid Resistance | | Satisfactory | |
| Thermal Conductivity | | х | |
| External Fire Performance | | х | |
| Durability | Abrasion | 4 | |
| | Resistance to Weathering | 2 | |
| Reaction to fire | | х | |

X = Not Relevant

10. The performance of the product identified in 1 and 2 is in conformity with the declared performance in 9.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in ${\bf 4}$.

Signed on behalf of the manufacturer:

T Mason

Brompton-on-Swale, North Yorkshire.

J Mason (Technical Manager) 1st August 2021

UK

Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY

21

UKCA 90

BS EN 1338:2003

Boot Kerb

Category II Concrete Paving Blocks

| Intended Use | External Flooring |
|---------------------------|-------------------|
| Emission of Asbestos | X |
| Breaking Strength | Pass |
| Slip / Skid Resistance | Satisfactory |
| Thermal Conductivity | X |
| External Fire Performance | X |
| Durability | Satisfactory |
| Reaction to fire | X |
| | |
| X = Not Relvant | |

See Declaration of Performance UKCA 90