

**DECLARATION OF PERFORMANCE
CE109**



1. Product Type: **Lakeland Derwentstone 50mm**
2. Identification: **Product ID code is shown on delivery ticket**
3. Intended Use: **Precast concrete paving block for use in external flooring applications**
4. Manufacturer: **Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY**
5. Authorised Representative: **Not applicable**
6. AVCP: **System 4**
7. Harmonised Standard: **EN 1338:2003**
8. ETA: **Not Relevant**
9. Declared Performance:

| Essential Characteristics | Performance | Harmonised technical specification | |
|---------------------------|--------------------------|------------------------------------|---|
| Intended Use | External Flooring | EN 1338:2003 | |
| Emission of Asbestos | X | | |
| Breaking Strength | 3.6 MPa | | |
| Slip/Skid Resistance | Satisfactory | | |
| Thermal Conductivity | X | | |
| External Fire Performance | X | | |
| Durability | Abrasion | | 4 |
| | Resistance to Weathering | | 2 |
| Reaction to fire | X | | |

X = Not Relevant

10. The performance of the product identified in 1 and 2 is in conformity with the declared performance in 9.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed on behalf of the manufacturer:

J Mason (Technical Manager)
Brompton-on-Swale, North Yorkshire. 1st March
2015



**Thomas Armstrong (Holdings) Ltd Workington Rd,
Flimby, Maryport, Cumbria. CA15 8RY**

13
CE109

EN 1338:2003

Lakeland Derwentstone 50mm

Category II Concrete Paving Blocks

| | |
|---------------------------|-------------------|
| Intended Use | External Flooring |
| Emission of Asbestos | X |
| Breaking Strength | Pass |
| Slip / Skid Resistance | Satisfactory |
| Thermal Conductivity | X |
| External Fire Performance | X |
| Durability | Satisfactory |
| Reaction to fire | X |

X = Not Relevant

See also Declaration of Performance **CE109**