

**DECLARATION OF PERFORMANCE
CE21**



1. Product Type: **Insulite Standard Block - 7.3N (including Sellite 'Thermal' Block)**
2. Identification: **Product ID code is shown on delivery ticket**
3. Intended Use: **In walls, columns and partitions**
4. Manufacturer: **Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY**
5. Authorised Representative: **Not applicable**
6. AVCP: **System 4**
7. Harmonised Standard: **EN 771-3 : 2011**
8. ETA: **Not Relevant**
9. Declared Performance:

| Essential Characteristics | | Performance | Harmonised technical specification |
|--|--|--|------------------------------------|
| Dimensions | Length, mm | 440 | EN 771-3 : 2011 |
| | Width, mm | Various - shown on the delivery documentation | |
| | Height, mm | 215 | |
| Dimensional Tolerance | | D1 (Flatness NPD, Plane Parallelism NPD) | |
| Configuration | Shape & features | NPD | |
| | Group according to EN 1996-1-1 (EC6) | Group 1 | |
| Compressive strength | Mean compressive strength, N/mm ² | 7.3 (⊥ bed face, whole unit) (Cat II) | |
| | Direction of load | Perpendicular to bed faces | |
| | Unit category | Category II | |
| Dimensional stability | Moisture Movement, mm/m | 0.6 | |
| Bond strength | Shear bond strength, N/mm ² | 0.15 with GPLM | |
| | Flexural bond strength | NPD | |
| Reaction to fire | | A1 (Commission Decision 2000/605/EC) | |
| Water absorption, gm ² .s ^{-0.5} | | NPD | |
| Water vapour permeability | | 5/15 (tabulated value) | |
| Direct airbourne sound insulation | Gross density, kg/m ³ | 1500 | |
| | Configuration; dimensions & tolerances | See configuration | |
| Thermal Conductivity, W/mK (λ _{10, dry}) ρ = 50% | | 0.44 <small>Dry value - design values require correction for moisture content. See product literature.</small> | |
| Durability against freeze / thaw | | For use below and above ground level | |
| Dangerous substances | | See Note | |

Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA of BS EN 771-4:2032

10. The performance of the product identified in 1 and 2 is in conformity with the declared performance in 9.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed on behalf of the manufacturer:

J Mason (Technical Manager)
Brompton-on-Swale, North Yorkshire. 1st June 2013



Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY

13

CE21

EN 771-3 : 2011

Insulite Standard Block - 7.3N (including Sellite 'Thermal' Block)

Category II aggregate concrete masonry unit

| | | |
|--|--|--|
| Dimensions | Length, mm | 440 |
| | Width, mm | Various - shown on the delivery documentation |
| | Height, mm | 215 |
| Dimensional Tolerance | Category | D1 (Flatness NPD, Plane Parallelism NPD) |
| Configuration | Shape & features | NPD |
| | Group according to EN 1996-1-1 (EC6) | Group 1 |
| Compressive strength | Mean compressive strength, N/mm ² | 7.3 (⊥ bed face, whole unit) (Cat II) |
| | Direction of load | Perpendicular to bed faces |
| | Unit category | Category II |
| Dimensional stability | Moisture Movement, mm/m | 0.6 |
| Bond strength | Shear bond strength, N/mm ² | 0.15 with GPLM |
| | Flexural bond strength | NPD |
| Reaction to fire | | A1 (Commission Decision 2000/605/EC) |
| Water absorption, gm ² .s ^{-0.5} | | NPD |
| Water vapour permeability | | 5/15 (tabulated value) |
| Direct airbourne sound insulation | Gross density, kg/m ³ | 1500 |
| | Configuration; dimensions & tolerances | See configuration |
| Thermal Conductivity, W/mK (λ _{10, dry}) ρ = 50% | | 0.44 <small>Dry value - design values require correction for moisture content. See product literature.</small> |
| Durability against freeze / thaw | | For use below and above ground level |
| Dangerous substances | | See Note |

Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA of BS EN 771-4:2032

See also Declaration of Performance **CE21**