

# DECLARATION OF PERFORMANCE

## UKCA 62



- Product Type: **Type F Rebate Block**
- Identification: **Product ID code is shown on delivery ticket**
- Intended Use: **In walls, columns and partitions**
- Manufacturer: **Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY**
- Authorised Representative: **Not applicable**
- AVCP: **System 4**
- Designated Standard: **BS EN 771-3 : 2011**
- ETA: **Not Relevant**

9. Declared Performance:

Essential Characteristics		Performance	Designated technical specification
Dimensions	Length, mm	440	BS EN 771-3 : 2011
	Width, mm	140	
	Height, mm	150	
Dimensional Tolerance		D1 (Flatness NPD, Plane Parallelism NPD)	
Configuration	Shape & features	NPD	
	Group according to EN 1996-1-1 (EC6)	Group 1	
Compressive strength	Mean compressive strength, N/mm <sup>2</sup>	7.3 (⊥ bed face, whole unit) (Cat II)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability	Moisture Movement, mm/m	0.6	
Bond strength	Shear bond strength, N/mm <sup>2</sup>	0.15 with GPLM	
	Flexural bond strength	NPD	
Reaction to fire		A1 (Commission Decision 2000/605/EC)	
Water absorption, gm <sup>2</sup> .s <sup>-0.5</sup>		NPD	
Water vapour permeability		5/15 (tabulated value)	
Direct airbourne sound insulation	Gross density, kg/m <sup>3</sup>	2000	
	Configuration; dimensions & tolerances	See configuration	
Thermal Conductivity, W/mK (λ <sub>10, dry</sub> ) ρ = 50%		1.05 Dry value - design values require correction for moisture content. See product literature.	
Durability against freeze / thaw		For use below and above ground level	
Dangerous substances		See Note	
Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA of BS EN 771-3:2011			

10. The performance of the product identified in 1 and 2 is in conformity with the declared performance in 9.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed on behalf of the manufacturer:

J Mason (Technical Manager)

*J Mason*

Brompton-on-Swale, North Yorkshire.

1st August 2021



Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY

21

UKCA 62

BS EN 771-3 : 2011

## Type F Rebate Block

Category II aggregate concrete masonry unit

Dimensions	Length, mm	440
	Width, mm	140
	Height, mm	150
Dimensional Tolerance	Category	D1 (Flatness NPD, Plane Parallelism NPD)
Configuration	Shape & features	NPD
	Group according to EN 1996-1-1 (EC6)	Group 1
Compressive strength	Mean compressive strength, N/mm <sup>2</sup>	7.3 (┴ bed face, whole unit) (Cat II)
	Direction of load	Perpendicular to bed faces
	Unit category	Category II
Dimensional stability	Moisture Movement, mm/m	0.6
Bond strength	Shear bond strength, N/mm <sup>2</sup>	0.15 with GPLM
	Flexural bond strength	NPD
Reaction to fire		A1 (Commission Decision 2000/605/EC)
Water absorption, gm <sup>2</sup> .s <sup>-0.5</sup>		NPD
Water vapour permeability		5/15 (tabulated value)
Direct airborne sound insulation	Gross density, kg/m <sup>3</sup>	2000
	Configuration; dimensions & tolerances	See configuration
Thermal Conductivity, W/mK (λ <sub>10, dry</sub> ) ρ = 50%		1.05 Dry value - design values require correction for moisture content. See product literature.
Durability against freeze / thaw		For use below and above ground level
Dangerous substances		See Note
Note: Information on Dangerous Substances will only be given when and where required in the appropriate form. See Annex ZA of BS EN 771-3:2011		

See Declaration of Performance: UKCA 62